
Mobile Computer

Sleek Consumer Style Look On The Outside, Compelling Enterprise Benefits Inside

- Compact & Sleek Design
- Enhanced Durability & Lifecycle
- Supported by BOS™ Enterprise Solutions
- High-Capacity Battery, Power for Hours
- Multi-Touch Support



Operation Temp -20°C to 50°C -4°F to 122°F

Camera 13MP Autofocus with flash 5MP Fixed Focus



Key Features

Sleek & Portable

SF650 features an ultra-thin, Bezel-less design complimenting the sleek consumer-style look.

Supported by BOS™Enterprise Solutions

Bluebird BOS[™] (Business Optimizing Solutions) is supported with the purchase of this device. You can access specialized applications in Business such as PTT Express, Wi-Fine[™], Provisioning & Staging solutions without additional cost. These services are an accumulation of Bluebird's know-how and experience of over 2 decades.

High-Capacity Smart Battery, Power for Hours

With a 5000mAh battery and PowerManagerTM, one of many Bluebird BOSTM Solutions offered with this device, the running-time on the SF650 has a significant advantage when compared to its competitors.

Always Connected

Whether indoors or in the field, the SF650 is connected wherever it goes. The SF650 provides exceptional network connectivity with support for cellular, Wi-Fi, and Bluetooth.



Industry & Applications

- Healthcare
- EMR/EHR
- Pharmacy Management Retail
 - etail
- Customer Engagement
- BOPIS (Buy online, Pick up in store)
- Shelf Management
- Backroom Management
- Hospitality
- Order Taking

BOS[™]Solutions & Software

- BOS™ Provisioning
- BOS™ Staging
- BOS™ Kiosk
- BOS™ Virtual Key
- BOS™ Enterprise Keyboard
- BOS™ VoIP, PTT, PTT Express
- BOS™ EMM
- BOS™ Wi-Fine™
- (WIFI analyze application)
- BOS™ SecureID

3'rd Party Solutions Integration

- EMM : Airwatch, MobileIron, Mobicontrol, IBM Mass360, XenMobile
- PTT : ESChat, Zello, IMPTT, EveryTalk, AirPTT

Bluebird Warranty Service

- BluebirdCare™
- BluebirdCare™ TSC

Specifications

PERFORMANCE CHARACTERISTICS

CPU	2.0 GHz Octa Core Processor
Operating System	Android 12; Upgradeable to Android 13
Memory	4GB RAM / 32GB Flash
	3GB RAM / 32GB Flash(Optional)
PHYSICAL CHARA	CTERISTICS
Dimensions (L x W x D)	169 x 77.8 x 9.9 mm
Weight	210g
Display	6.5" HD+ (1600 x 720), TFT-IPS
Backlight	LED backlight
Power	User replaceable battery, 5000mAh/3.85v
Expansion Slot	MicroSD 32GB SDHC, up to 128GB SDXC
SIM	1 Nano SIM
Interface	USB Type C Connector (USB 2.0)
Notification	Audible tone; multi-color LEDs; vibration
Keypad	On-screen keypad and Enterprise Keyboard power button; volume up/down buttons
Voice and Audio	Dual noise-cancelling microphones; High-quality speaker phone, 3.5mm headset jack
WIRELESS WAN	
	One Global SKU
Radio Frequency Band	LTE-FDD : B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 LTE-TDD: B38, B39, B40 WCDMA : B1, B2, B4, B5, B8, B19 GSM : 850, 900, 1800, 1900
GPS	(for WWAN only) A-GPS, GLONASS, BEIDOU, Galileo
WIRELESS LAN	
Radio	802.11 a/b/g/n/ac, 2.4 GHz + 5 GHz Wi-Fi™ certified; Wi-Fi hotspot
WIRELESS PAN	

Camera	Rear : 13MP Autofocus with flash Front : 5MP Fixed Focus (Optional) Rear: 5MP Autofocus with Flash Front: 5MP Fixed Focus
NFC	ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards, MiFare
SENSOR	
Light Sensor	Ambient Light
Motion Sensor	Proximity, Gyro, Accelerometer, E-Compass
USER ENVIRONME	NT
Operating Temp	-20°C to 50°C / -4°F to 122°F
Storage Temp	-30°C to +70°C/ -22°F to +158°F
Humidity	95% non-condensing
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
ACCESSORIES	
Additional	Power adapter, Adapter plug, USB C Cable
	Neck Strap Standard Protective Case Soft Plastic Screen Guard

3F,115, Irwon ro, Gangnam gu, Seoul, Republic of Korea, Postal#06355 Phone. +82-1577-0778 Fax. +82.2.6499.2242 Copyright © Bluebird Inc. All rights reserved. Bluebird Inc. is the designer and manufacturer of Bluebird handheld mobiles. Bluebird logo is registered trademark of Bluebird Inc. All other trademarks are property of their repective owners.

